

I CLAIM:

27. A method of moulding a golf club head comprising:
 - a) positioning weights within a mould;
 - b) positioning a shaft anchoring element within said mould;**
 - [b] c) moulding a main body around said weights and said shaft anchoring element,** including forming a shaft receiving bore in said main body **through said anchoring element;** and
 - [c] d) forming a front face [front insert receiving pocket] on said main body;** and
 - d) inserting an insert into said insert receiving pocket; and]
28. A method of moulding a golf club head as claimed in claim 27, wherein said step of positioning said weights comprises mounting said weights upon [a] **one or more** mounting pin to securely position the weights in the mould.
29. A method of moulding a golf club head as claimed in claim 27, wherein said step of forming **front face** [front insert pocket] includes moulding **a** [said] front insert pocket in a first moulding step.
30. A method of moulding a golf club head as claimed in claim 27, wherein said step of forming **front face** [front insert pocket] includes machining **an** [said] insert pocket into a front face of said moulded main body.
31. A method of moulding a golf club head as claimed in **claims 29 or 30** [claim 27, wherein said] **further including** a step of inserting [said] **an** insert into said insert receiving pocket [comprises] **by** moulding said insert into said front insert receiving pocket.
32. A method of moulding a golf club head as claimed in claim [27] **31**, further including a step of finishing said [club] **front** face which step includes machining a desired loft and grooves into the front face [of the moulded insert and club face].

BEST AVAILABLE COPY
BEST AVAILABLE COPY

33. (new claim) A method of moulding a golf club head as claimed in claim 27 further including the step of providing an attachment screw generally perpendicular to said shaft receiving bore.

34. (new claim) A method of moulding a golf club head as claimed in claim 27 further including the step of passing said attachment screw through said shaft anchoring element into said shaft receiving bore.

and

BEST AVAILABLE COPY